

BID SPECIFICATIONS
Sidewalk Repair/Concrete Work

SPECIFICATIONS:

Sidewalk is to be 4 or 5 ft. wide and 4 inches thick except at driveways where thickness shall be 6 inches. Please see attached sidewalk detail for requirements. All work completed must match current grade and include rumble segments (truncated domes as indicated in detail sheets may be substituted with city approval) at each street intersection. Sidewalk repair may require removal of old sidewalk and possible haul away of debris. Debris can be transported to city garage at discretion of Public Works Director. Sections that are in good condition may be left and worked around at the discretion of the city. Bids must be submitted by cost per sq. ft. for demolition and construction separately. Please note any additional fee items including equipment, etc. Concrete will be included at time of construction at current market value and is not to be included in construction prices on bid form. The expected amount of sidewalk to be repaired is approximately 4000 linear feet, but total length of repair is at the discretion of the city. Work is intended to be completed by December 31, 2025. Bid form must be filled out completely to be considered. Bidders may call for an appointment to look at sidewalk locations with Public Works Director.

Additional concrete work may be completed at the discretion of the city based on the unit price as presented for sidewalks.

UTILITIES

Utility owners will adjust all sewer manhole castings, water and gas valve boxes and drainage grates within the sidewalk to proposed grade prior to repair.

The contractor will provide all necessary protective measures to safeguard existing utilities from damage during the construction of this project. In the event that special equipment is required to work over and around the utilities, the contractor will be required to furnish such equipment.

The contractor shall notify each individual utility owner of his plans of operation in the area of utilities prior to commencing work. The contractor shall contact the utility owners and request them to properly locate their respective utility on the ground. This notification shall be given at least three (3) business days prior to commencement of operations around the utility.

Underground utilities can be located by all The Tennessee One Call System at 811.

MISCELLANEOUS

Prior to construction, the contractor shall be responsible for insuring that all required federal, state and local permits and approvals have been obtained. No construction or fabrications shall begin until the contractor has received and thoroughly reviewed all plans and other documents approved by all applicable permitting authorities.

Any property damage caused by the contractor or his operations shall be corrected and/or restored to the satisfaction of the property owner and the engineer at no additional cost to the owner.

Street signs, mailboxes, etc. shall be relocated as necessary by the contractor. All cost to be included in other items of work.

The contractor shall take the necessary measures to provide for the safety and convenience of the general public and the residents along the proposed construction route while work is in progress.

Notice to Bidders

The City of Algood will receive sealed Bids until 10:30 a.m. Thursday, May 1, 2025, for sidewalk repair/concrete work. No faxed bids or e-mailed bids will be accepted. No bids will be accepted after 10:30 a.m. (CST). Bid opening will be Thursday, May 1, 2025, at 10:30 a.m. (CST) at Algood City Hall.

Specifications may be obtained by contacting the City of Algood, at 931-537-9545, online at www.algood-tn.com, or email keith.morrison@algoodtn.gov.

All bids must be mailed or delivered to the City of Algood, ATTN: Bid Opening, 215 W Main Street, Algood, TN 38506. All envelopes must be sealed and marked "Sidewalk Repair/Concrete Work 2025".

City of Algood reserves the right to reject any or all bids.

Keith Morrison,
City Administrator

Bid Form

ALL ITEMS ON THIS FORM WILL BE USED IN EVALUATION OF BIDS

Typical sidewalk 4" thick (per sq. ft.) _____

Driveway Crossing 6" thick (per sq. ft.) _____

Concrete Curb (per ln. ft.) _____

Pedestrian Ramp 4' x 2' with Truncated Domes or acceptable substitute (per section)

Equipment Fees: _____

Demolition (per sq. ft.) with haul away _____

City provide location for debris _____

Note Exceptions Taking and any additional information that may be considered in evaluating bid.

CONCRETE WILL BE INCLUDED WITH BILL FROM CONTRACTOR AT TIME

OF CONSTRUCTION AT CURRENT MARKET VALUE

Company Submitting Bid _____

Address _____ **Phone** _____

Company Representative _____ **Phone** _____

Email Address: _____

Fax Number: _____